

## Plenty Power Distribution Unit



### PRODUCT SPECIFICATION

**Important: Power sources must be in-phase!**

|                        |  |
|------------------------|--|
| ▶ Part number          | PLP1017                                    |
| ▶ Current rating (A)   | 10   |
| ▶ Voltage rating (VAC) | 250  |
| ▶ Housing material     | Steel , black                              |
| ▶ Dimensions (WxHxD)   | 19" x 1U x 132mm<br>(438mm x 43mm x 132mm) |
| ▶ Mounting             | Integrated 19" brackets                    |
| ▶ Data Outlet (front)  | RJ45 and subD 15p                          |
| ▶ Outlet Socket (rear) | 5x C13, 1x C19                             |
| ▶ Plug                 | 2x CEE 2p + E                              |
| ▶ Plug colour          | Blue                                       |
| ▶ Cable                | 2x H05VV F3G1,5mm <sup>2</sup>             |
| ▶ Cable length (m)     | 2x 3                                       |
| ▶ Cable colour         | Black                                      |
| ▶ Control              | IP Power Switch                            |

|                           |  |
|---------------------------|--|
| ▶ Network connection      | Ethernet   |
| ▶ Network protocol        | TCP/IP   |
| ▶ operate- / release time | Aprox. 15 / 15ms   |
| ▶ Pull in voltage         | 184 VAC  |
| ▶ Release voltage         | 92 VAC   |
| ▶                         |  |
| ▶                         |  |
| ▶                         |  |
| ▶ Extra info              | A and B feed. When A feed falls out, B feed takes over. When A feed comes back again, A feed takes over. |
| ▶                         |  |
| ▶                         |  |
| ▶ Marking                 | CE   |
| ▶ Weight (KG)             |  |
| ▶ Last modification       | 2009-04-09   |

Specifications subject to change without notice

