




<p>POM Series</p> <p>Inlet Power monitoring Per outlet monitoring Environmental monitoring</p>	<p>OUTPUT</p> <p>(24) IECC13 Locking (10A Rated) (6) C19 Locking (16A Rated)</p>	<p>OPERATING TEMPERATURE</p> <p>0° to 60°C</p>
<p>INPUT</p> <p>220VAC 32A 50HZ IEC60309 32A 3Pin plug 3M H07RN-F3G4.0mm² Power lead</p>	<p>BRANCH CIRCUITS</p> <p>(2) 2 Pole 16A Hydraulic-Magnetic Circuit Breaker</p>	<p>MOUNTING ACCESORIES</p> <p>(2) IPFIX001 (2) IPFIX002 (2) IPFIX006</p>

Revisions		
Rev	Description	Date

DRAWING TYPE  (NO PERMISSION, NO CHANGING)		PLH3040	
unit=mm		Housing	Aluminium
TECHNICAL STANDARD 1.IT11; 2.NO RUSTNESS 3.NO FLAW ON THE SURFACE			Black Powder coating
FILLET R0.5	ANGLE ±0.5°	 www.ratio-electric.com	
FIRST ANGLE 			
SCALE 1:3		DATE 24-03-2016	