



<p>POMS Series Inlet Power monitoring Per outlet monitoring and switching Environmental monitoring</p>	<p>OUTPUT (12) IECC13 Locking (10A Rated) (4) C19 Locking (16A Rated)</p>	<p>OPERATING TEMPERATURE 0° to 60°C</p>
<p>INPUT 250VAC 32A 50HZ IEC60309 32A 1Phase plug(blue) 3M H07RN-F3G4mm² Power lead</p>	<p>BRANCH CIRCUITS (2) 2 Pole Magnetic Hydraulic CB 16A</p>	<p>MOUNTING ACCESORIES (2) Metal Bracket</p>

Revisions		
Rev	Description	Date

<p>DRAWING TYPE (NO PERMISSION, NO CHANGING)</p>	<p>PLP4020</p>	
<p>unit=mm</p> <p>TECHNICAL STANDARD 1.IT11; 2.NO RUSTNESS 3.NO FLAW ON THE SURFACE</p>	<p>Housing</p>	<p>Steel t=1.5mm</p>
<p>FILLET R0.5</p> <p>ANGLE ±0.5°</p> <p>FIRST ANGLE</p>		<p>Black Powder coating</p>
<p>SCALE 1:3</p>	<p>Ratio ELECTRIC www.ratio-electric.com DATE 31-03-2016</p>	